

Product Information

6600 SFR Air-Bond™

Fast, Soft, Light Putty - Bodyfiller

silco
AUTOMOTIVE

Light

WEIGHT

1,3 kg/l

Sanding

AFTER 12 MINUTES

*without paper
clogging*



Dries

40% FASTER

*than other
putties*

Excellent

ADHESION ON

various substrates



Ultra fast drying putty for perfect refinish results within minutes.



**NON-POROUS,
SMOOTH SURFACE**

EASY APPLICATION

EASY SANDABILITY

6600 SFR Air-Bond™

Fast, Soft, Light Putty - Bodyfiller

DRYING TIME *

20°C

12 - 14 min

Potlife

3 - 4 min

**Indicative times subject to amount of hardener/application/environment.*

How to

APPLICATION

Treated surface must be clean, dry, rust-free and grease-free. Optimal adhesion can be achieved on well abraded surface. Mix the putty and hardener thoroughly until the colour is even. Use filler knife, plastic or rubber spatula for the application. Do not overdose! Excessive quantity of hardener can cause colour change on the topcoat and shorten the potlife. Hardener quantities below 2% can result in prolonged drying time.

For further and updated information please refer to the TDS published on www.silco-automotive.com.

Info

PRODUCT

Universal fast and soft lightweight polyester putty. Thanks to its cutting edge filling material technology, the specific weight of only 1.3 kg/L enables it to fill irregularities and dents with significantly less product (by weight) in comparison with conventional putties. It dries up to 40% faster than conventional putties.

Packaging

PUTTY & HARDENER

6600 SFR Air-Bond™

Fast, Soft, Light Putty - Bodyfiller

Prod. Nr.	Content	Color
6600-1,3	1.3 kg	White
BPO Hardener 2-3%	50 g	Red paste