

Product Information

9600 SFR X-Cure™

UHS 420 Ultra Rapid Clear Coat

silco
AUTOMOTIVE

Exceptionally
FAST DRYING
at 60° or 20°C

Only
5 MINUTES
at 60°C

Immediate
POLISHING
after cooling down



Perfect
GLOSS RETENTION
& UV protection

Very easy
APPLICATION
with 1:1 mixing
ratio

In the base coat
NO HARDENER/
ACTIVATOR
is needed



Ultra fast drying clear coat for perfect refinish results within minutes.



EASY APPLICATION



ULTRA FAST DRYING

9600 SFR X-Cure™

UHS 420 Ultra Rapid Clear Coat

Mixing ratio 1:1

HARDENER

Standard
9650

Slow
9670

DRYING TIME *

20°C 60 min 65 min

60°C 5 min 5 min

IR 5 - 7 min 5 - 7 min

Flash-off <5 min <5 min

Potlife 60 min 60 min

THINNER

No thinner is needed.

How to

APPLICATION

Use of slow hardener is recommended in case of higher temperatures in combination with larger surfaces. Light half coat followed by full closed coat without flash off can be used for spot and quick repairs. For all other repairs, use two full coats application method, with max. 5 minute flash off between coats.

For further and updated information please refer to the TDS published on www.silco-automotive.com.

Info

PRODUCT

Highly productive UHS clear coat X-Cure is characterised by outstandingly short drying times when baking (5 min/60°C) or when air drying (60 min/20°C). Polishing is possible immediately after cooling. Short drying times allow more turnover of vehicles and decreased manpower costs. Additionally, fast drying without oven baking allows fuel and electricity savings.

Packaging

CLEAR COAT

9600 SFR X-Cure™

UHS 420 Ultra Rapid Clear Coat

Prod. Nr.	Content
9600-1 / 9600-2,5 / 9600-3,78 / 9600-5	1 L / 2.5 L / 3.78 L / 5 L

HARDENER

9650 - 9670 UHS Hardener

UHS Acrylic Hardener - mixing ratio 1:1

Prod. Nr.	Content	Description
9650-1 / 9650-2,5 / 9650-3,78	1 L / 2.5 L / 3.78 L	Standard
9670-2,5 / 9670-3,78	2.5 L / 3.78 L	Slow