

3005 Cavity Coat Spray

Protective coating based on special waxes in spray. High melting-point prevents draining off at higher summer temperatures.

- strong adhesion and penetration into all vehicle cavities
- long-term protection from corrosion and noise
- does not contain silicones

Packaging

Product no.	Description	Volume/Weight	Packaging [pcs/box]
3005-0,5	Colourless	500 ml	12

Shelf life

Min. 24 months from the production date under normal storage conditions and unopened can.

Additional information

FOR PROFESSIONAL USE ONLY!

Always read the instructions.

IMPORTANT: This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.



Technical data sheet

2023-3

3005 Cavity Coat Spray