

## **1410 Seam-Seal**


**1K brushable sealant based on PU. After curing, it forms a strong, elastic, crack-resistant mass and serves as an effective protection against water and moisture.**

- overpaintable with solvent-based or water-based varnishes
- resistant to water, oil, gasoline
- quick drying

### **Substrate preparation**

Clean, dry and degrease the surfaces with a suitable anti-silicone cleaner. Metal surfaces must be pre-applied with an anti-corrosion primer, allowed to dry and then sealed.

### **Mixing ratio**



The product is ready for use!

### **Spraygun setup**



Application type :	Brushable
Number of coats:	1
Optimal application temperature:	15-35°C

### **Drying**



Ready to be painted (25°C, 1 mm thickness)	24 h
Skin time:	3-4 min

### **Packaging**

Product number	Description	Volume/Weight	Packaging
1410-0,85	Gray	0,85 kg	12

### **Volatile organic compounds**

The VOC value for this product is 348 kg/L



# 1410 Seam-Seal

## Shelf life

---

At least 18 months from date of manufacture when stored normally between 15°C and 30°C and in unopened packaging

## Additional information

---

FOR PROFESSIONAL USE ONLY!

Always read the instructions.

**IMPORTANT:** This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.